

P20000HD



Phone: 402-693-2599

P20000HD

Fax: 402-693-2681

The 20,000 Series Pump Hoist consists of a 36 ft. self-supporting telescoping mast held by two 4" x 48" double acting cylinders. This design eliminates the need for guy cables. Maximum layback is 8 ft. The basic rig consists of 18,000 lb. capacity (9,000 lb. single line), 180 ft. of 9/16" Dyform 18 HSLR rotation resistant cable, open swage socket with 7 ton swivel hook, hydraulic outriggers with lock valves, line parting block and 11 ton swivel hook, automatic engine speed control, and double gear pto with direct mount heavy duty gear pump. Maximum single line speed is 135 fpm. (Triple line capacity 27000 lbs available with optional guide cable kit)

Standard Features:

- **Self-contained and sealed oil bath planetary drive**
 - 30 gallon hydraulic reservoir
 - In-line cable weights
 - 2,000 Series Char Lynn hydraulic motors (for added efficiency)
 - Outside left oriented control handles (increased cargo bay storage)
 - 60" rear outrigger width
 - **Failsafe hydraulic disc brakes**
 - Failsafe over-center hydraulic holding valves
 - Extra high grade urethane paint
 - Tailout winch with 125 ft. of 3/8" cable and swivel hook
 - **Tower Load Status Gauge**
-

Optional Features:

- Remote control
- Sandreel
- Power to the rear
- Hydraulic wire winders
- Heavy duty tailgate
- Heavy duty pipe racks
- Front outrigger
- Hydraulic oil cooler
