

# P4000



**PULSTAR MANUFACTURING COMPANY**  
**P4000**  
**Phone: 402-693-2599 Fax: 402-693-2681**

The 4,000 Series Pump Hoist consists of a 32 ft. self-supporting mast held by two 3-1/2" x 48" double acting cylinders. This design eliminates the need for guy cables. Maximum lay-back is 10 ft. The basic rig consists of a 4,000 lb. capacity (2,000 lb. single line), 125 ft. of 3/8" rotation resistant cable, open swage socket with 3 ton hook, mast cylinder holding valves, and double gear pto with direct mount heavy duty gear pump for manual trans. Maximum single line speed is 105 fpm.

#### **Standard Features:**

- Self-contained and sealed oil bath gearcase
- 18 gallon hydraulic reservoir
- In-Line cable weights
- Tower Load Status Gauge
- 2,000 Series Char Lynn hydraulic motor (for added efficiency)
- 1/2" plumbing and high pressure hydraulic hoses
- Outside left oriented control handles (increased cargo bay storage)
- 60" rear outrigger width
- Failsafe hydraulic braking
- Failsafe over-center hydraulic holding valves
- Extra high grade urethane paint
- Mast cylinder holding valves

#### **Optional Features:**

- Sandreel
- Power to the rear
- Hydraulic wire winders
- Heavy duty tailgate
- Heavy duty pipe racks
- Front outrigger
- Hydraulic oil cooler