

P7000



PULSTAR MANUFACTURING COMPANY
P7000
Phone: 402-693-2599 Fax: 402-693-2681

The 7,000 Series Pump Hoist consists of a 37 ft. self-supporting mast held by two 3-1/2" x 48" double acting cylinders. This design eliminates the need for guy cables. Maximum layback is 11 ft. The basic rig consists of 7,000 lb. capacity (3,500 lb. single line), 175 ft. of 7/16" rotation resistant cable, open swage socket with 5-ton hook, mast cylinder holding valves, and double gear pto with direct mount heavy duty gear pump. Maximum single line speed is 150 fpm.

Standard Features:

- Self-contained and sealed oil bath gearcase
- 18 gallon hydraulic reservoir
- In-line cable weights
- Tower Load Status Gauge
- 2,000 Series Char Lynn hydraulic motor (for added efficiency)
- 1/2" plumbing and high pressure hydraulic hoses
- Outside left oriented control handles (increased cargo bay storage)
- 60" rear outrigger width
- Failsafe hydraulic braking
- Failsafe over-center hydraulic holding valves
- Extra high grade urethane paint
- Mast cylinder holding valves

Optional Features:

- Sandreel
- Power to the rear
- Hydraulic wire winders
- Heavy duty tailgate
- Heavy duty pipe racks
- Front outrigger Hydraulic oil cooler