

Super Six



PULSTAR MANUFACTURING COMPANY

Super Six

Phone: 402-693-2599 Fax: 402-693-2681

The Super Six Series Pump Hoist consists of a 32 ft. self-supporting mast held by two 4" HD double acting hydraulic cylinders. This design eliminates the need for guy cables. Maximum layback is 10 ft. The basic rig consists of a 4,000 lb. capacity (2,000 lb. single line), 125 ft. of 3/8" rotation resistant cable, open swage socket with 3 ton hook, and double gear pto with direct mount heavy duty gear pump for manual trans. Maximum single line speed is 160 fpm. (Triple line capacity 6000 lbs available with optional guy cable / block option.)
Dry Weight 2000#

Standard Features:

- Self-contained hyd. motor / brake direct drive winch
- In-Line cable weight
- Tower Load Status Gauge
- 2,000 Series Char Lynn hydraulic motor (for added efficiency)
- Remote Control
- Failsafe hydraulic braking
- Failsafe over-center hydraulic holding valves
- Mast cylinder holding valves

Optional Available Features:

- Guy cable / block kit
- Power to the rear
- Front outrigger (on some trucks)
- Breakout wrench
- Hydraulic oil cooler
- Mast light kit with brush guards
- Pipe racks with rack straps
- Other various options per price list

Remote Control *with adjustable response feature*