



PULSTAR MANUFACTURING COMPANY

Phone: 402-693-2599

P75000

Fax: 402-693-2681

(A1) P75000 basic rig includes the **standard primary mainline** and EXHD rotation resistant highly compacted cable, traveling block, outrigger and mast cylinder lock valves, 44 ft mast height, 12,500 lb max single line pulling capacity, 380 fpm max single line winch speed, 2-speed motors, electric shift on the fly

- Add tapered roller bearing eye and hook swivel
- Add Lebus split sleeve grooving
- Add remote control and pendant
- Add special operator side control
- Additional mast height (per foot)
- Cathead with hydraulic source
- Breakout with hydraulic source
- Dual front outriggers w/lock valves
- Hydraulic source for power tongs
- Power tongs handler jib boom
- Hydraulic oil cooler w/auto on/off function
- Rig complete lighting package
- Factory mount (petroleum base fluid)
- Factory mount (synthetic base fluid)
- Delivery charge per mile (includes permits)
- Startup technician charge
- Flatbed, cab cover, headache rack, matboard holders, underbody toolboxes, HD rear bumper
- Special paint color package
- Utility pneumatics plumbed to rear w/outlet

(A2) P75000 **optional secondary mainline** and EXHD rotation resistant highly compacted cable, traveling block, 16,700 lb max single line pulling capacity, 300 fpm max single line winch speed, 2-speed motors, electric shift on the fly

- Add tapered roller bearing eye and hook swivel
- Add Lebus split sleeve grooving
- Add remote control and pendant
- Add special operator side control

(A3) P75000 sandline#1, less cable and hook, 4000 lb max single line pulling capacity, 400 fpm max single line winch speed

- Sandline#2
- Sandline#3
- Sandline#4
- Sandline#5
- Sandline#6
- Add Lebus split sleeve grooving
- Add remote control and pendant
- Add special operator side control